

# **PINERIDGE SPEEDWAY CROWN VIC RULES**

2025 CROWN VIC RULES GENERAL THERE WILL BE A \$5,000 CLAIM RULE ON TOTAL CAR CLAIMED.

DRIVER MAY REMOVE SEAT AND BELTS. BODY BUMPERS MUST HAVE TOW CHAINS FRONT AND REAR MAY RUN TUBULAR BUMPER, SQUARE OR ROUND BUT MUST BE 2" OR SMALLER. MAY BE NO LONGER THAN 64". MAY RUN 1 LOOP BAR ON TOP OF BUMPER NO TALLER THAN 12" AND NO WIDER THAN 42". BUMPER MAY NOT EXTEND MORE THAN 8" FROM FRONT OF CHASSIS (MUST BE CENTERED SIDE TO SIDE AND VERTICALLY). NO PUSH BARS IN FRONT OR REAR OF CAR HOOD AND TRUNK MAY UTILIZE STOCK HINGES, BUT MUST BE SECURED WITH HOOD PINS NO HULLING OR LIGHTENING OF BODY.

THE ONLY AREAS ON CAR THAT MAY BE HULLED ARE THE FRONT DRIVER AND PASSENGER DOORS FRONT FENDERWELLS MAY BE REMOVED. ALL FLAMMABLE MATERIALS AND GLASS MUST BE REMOVED ANY HOLES IN FRONT FIREWALL AND REAR FIREWALL MUST BE COVERED WITH ALUMINUM OR STEEL ALL CARS MUST HAVE NUMBERS ON FRONT DOORS AND ROOF STEERING COLUMN MUST REMAIN STOCK, ALL AIRBAGS MUST BE REMOVED. QUICK RELEASE STEERING WHEEL OK, BUT MUST BE MOUNTED TO STOCK STEERING COLUMN. SHEET METAL DASH ALLOWED BUT CAN BE NO MORE THAN 14" DEEP (ABSOLUTELY NO DECKING). MUST HAVE AT LEAST 4 VERTICAL WINDSHIELD BARS IN FRONT OF DRIVER ROLL CAGE MUST BE INSIDE DRIVER COMPARTMENT ONLY, NO PART OF CAGE MAY EXTEND OUTSIDE OF PASSENGER COMPARTMENT

FOUR DRIVER DOOR BARS AND 3 PASSENGER DOOR BARS MINIMUM CAGE MUST BE SECURELY MOUNTED TO FRAME SUSPENSION NO ALTERING OF STOCK SUSPENSION ENGINE/ TRANSMISSION ENGINE MUST BE COMPLETELY STOCK 4.6 SOHC

MUST HAVE MUFFLERS EXHAUST MUST EXTEND TO REAR TIRES. CATALYTIC CONVERTOR MAY BE REMOVED TRANSMISSION MUST BE COMPLETELY STOCK A.C. CONDENSOR BYPASS LINES MUST BE DISCONNECTED. SAFETY DRIVERS MUST WEAR FULL FIRE SUIT, RACING GLOVES, RACING SHOES AND HELMET WHILE ON TRACK. HANS DEVICE RECOMMEND RACING SEAT AND BELTS MANDATORY RACING BELT MUST HAVE 5 POINT SYSTEM FIRE EXTINGUISHER REQUIRED IN ALL CARS BATTERY MAY BE IN STOCK LOCATION OR RELOCATED TO TRUCK, NO BATTERIES INSIDE COCKPIT/PASSENGER COMPARTMENT. BATTERY DISCONNECT SWITCH ON THE DRIVER SIDE, REAR SPEAKER AREA.

ALL CARS MUST HAVE WINDOW NET TIRES/WHEELS TIRES MUST BE DOT LEGAL AND ALL 4 TIRES MUST BE THE SAME SIZE WHEELS MUST BE STOCK STEEL OR AFTERMARKET 7 INCH BY 4 INCH OFFSET DOT APPROVED WHEELS AND ALL 4 WHEELS MUSTBE SAME SIZE AND OFFSET NO WHEEL SPACERS OF ANY KIND WEIGHT NO ADDING BALLAST OF ANY TYPE TO CAR, BRAKES MUST REMAIN FACTORY STOCK, ALL 4 CORNERS MUST BE OPERABLE REAREND MUST BE FACTORY STOCK REAREND WITH STOCK COMPONENTS THE ONLY LEGAL GEARS WILL BE 2.73, 3.27, AND 3.55. REAR DIFFERENTIAL MAY BE LOCKED BY ANY MEANS NECESSARY, BUT GEAR RATIO RULE REMAINS THE SAME (3.55 MAX GEAR) FUEL PUMP GAS ONLY, NO RACING FUEL, NO E-85 AT ALL, NO ADDITIVES STOCK FUEL TANK AND FUEL PUMP ONLY TECH TOP 3 WILL ALL BE TECHED WITH DRIVERS AND TRACK TECH MAN AFTER FEATURE.

THE ABSENCE OF A SPECIFIC RULE DOES NOT IMPLY APPROVAL, CONSENT OR PERMISSION REGARDING THAT SUBJECT. ANY QUESTIONS OR DOUBTS REGARDING SUCH MATTERS SHOULD BE DIRECTED TO RACE TRACK OFFICIALS FOR A CLARIFICATION.